

AASHTO T 283

Pavegrip 425

High Performance
Acidic Antistripping Additive

SUPERPAVE

Pavegrip – GET A GRIP ON THE REQUIRED TSR OF TODAYS TOUGH MIX DESIGNS

Product: Pavegrip 425 is a concentrated 100% active liquid antistripping additive. It's Organophosphorous compound formulation makes this product compatible with Polyphosphoric Acid modified asphalts.

Benefits: SUPERPAVE Moisture Sensitivity Testing - Significantly improves Tensile Strength Ratio results in the AASHTO T-283 test procedure

Easy to use liquid – Unlike lime, it does not increase dust content and lower the voids in the mineral aggregate (VMA). Also, being a liquid it can be metered or pumped using a gear or displacement pump.

Properties:	Viscosity @ 77°F cs	1500- 2500
	Specific Gravity @ 77°F	0.93 ± 0.04
	Weight, lbs/gal @ 77°F	7.76 ± 0.33
	Flash Point (ASTM D92)	> 300°F
	Pour Point (ASTM D97)	16°C/60°F

Storage and Handling Always refer to the product MSDS prior to handling. Pavegrip 425 is a DOT regulated product. Pavegrip 425 must be stored in a tank that is designed for acid service. The recommended storage temperature is 100° to 120° F. Packaging includes 55 gallon drums (440 pounds net), 275 gallon totes (2,205 pounds net) or in various bulk quantities.