

**AASHTO T 283**

## **Pavegrip 519**

**High Performance  
Antistripping Additive**

**SUPERPAVE**

### **Pavegrip – GET A GRIP ON THE REQUIRED TSR OF TODAYS TOUGH MIX DESIGNS**

**Product:** Pavegrip 519 is a concentrated 100% active liquid antistripping additive. It's 100% active formulation makes this low odor, heat stable product a high performance additive that can help with even the most difficult mix designs.

**Benefits:** SUPERPAVE Moisture Sensitivity Testing - Significantly improves Tensile Strength Ratio results in the AASHTO T-283 test procedure

Easy to use liquid – Unlike lime, it does not increase dust content and lower the voids in the mineral aggregate (VMA). Also, being a liquid it can be metered or pumped using a gear or displacement pump.

<b>Properties:</b>	Viscosity @ 77°F cs	100- 200
	Specific Gravity @ 77°F	1.00 ± 0.04
	Weight, lbs/gal @ 77°F	8.33 ± 0.33
	Flash Point (ASTM D92)	342°F
	Pour Point (ASTM D97)	0°C/32°F

**Storage and Handling** Always refer to the product MSDS prior to handling. Pavegrip 519 is a DOT regulated product. Pavegrip 519 can be stored in a mild steel tank. The recommended storage temperature is 100° to 120° F. Packaging includes 55 gallon drums (440 pounds net), 275 gallon totes (2,205 pounds net) or in various bulk quantities.